

20k Rotary Shotgun Nozzles

SURFACE PREP



Barracuda®

- No air required
- Rotation speed control
- 2 or 4 jet configuration
- Easy field maintenance
- Replaceable nozzle tips
- Less than 3 lbs full weight
- Less maintenance than air-powered tools

20k psi Models

The **Barracuda®** sinks its teeth into tough cleaning jobs. Our leak-free seal design combined with centrifugal rotation speed control delivers more power to the surface for superior results.

The **Barracuda®** is excellent for difficult and irregular surfaces where a hand-held operator can more efficiently maneuver the cleaning head. We recommend 4-port heads for larger surface areas with thin coating removal and 2-port heads for removal of thick deposits.

The **BC-K** and **BC-K-P2** both operate from 2k-20k psi and come with a 2-jet or 4-jet head configuration respectively. As with most **StoneAge®** tools, they are sold with replaceable nozzle tips.



US Patent 5,909,848 and International Patents.



A 4-jet configuration at work on a tube bundle.

20k psi Barracuda® Specifications

MODEL	MAX. PRES.	MAX. FLOW	LENGTH	DIAMETER	INLET	JETS
BC-K	20k psi	15 gpm	78 in.	1.8 in.	9/16 MP	2 x AP4
	1400 bar	57 lpm	200 mm	46 mm		
BC-K-P2	20k psi	15 gpm	78 in.	1.8 in.	9/16 MP	4 x AP2
	1400 bar	57 lpm	200 mm	46 mm		

Barracuda 20k psi - Jetting Chart

		NOZZLE ID in inches													
		.018	.020	.022	.024	.026	.029	.032	.035	.038	.042	.047	.052		
PRESSURE in K psi	10							5.5	6.5	7.6	9.2	11.4	Jetting Flow in gpm 2-Jet Model - BC-K 1/4 npt ports		
	15					4.4	5.5	6.7	8.0	9.4					
	20				4.4	5.1	6.4	7.7							
	10			5.2	6.1	7.2	8.8	10.6					Jetting Flow in gpm 4-Jet Model - BC-K-P2 1/8 npt ports		
	15	4.3	5.2	6.3	7.5	8.8									
	20	4.9	6.1	7.3											



ADVANCED PRESSURE SYSTEMS

1-877-290-4277 ▲ FAX: 281-290-9952

www.advancedpressuresystems.com


E-mail orders: sales@advancedpressuresystems.com



40k Rotary Shotgun Nozzles

40k psi Barracudas - Ultra High Pressure

The **Barracuda**® **BC-H9-C** and **BC-H9LF-C** can handle pressures from 28k-40k psi. Both of these models feature 4 jets with speed control rotation. These self-rotary tools eliminate the need for compressed air. The **BC-H9-C** is for 4-8 gpm and the **BC-H9LF-C** is for 3-4 gpm.



NEW

**Now Get
Longer Seal Life!**

New BC 505 Cartridge Design

StoneAge® is proud to announce that we have upgraded the cartridge assembly for the **BC-H9-C**. This new **BC 505** will retrofit into your existing 40k psi **Barracuda**®, **Gopher** and **SL** tools and is supplied with all new tools. This upgrade is designed to increase the operational life of the high pressure seals.

The new system reduces down-time and improves accessibility to wear items. Now operators can have a backup cartridge on-hand which can be installed in minutes. Then the old cartridge can be field serviced and ready for re-installation when needed.



Safe and effective surface preparation.



40k models feature a replaceable cartridge seal.

SURFACE PREP

40k psi Barracuda Specifications

MODEL	MAX. PRES.	MAX. FLOW	LENGTH	DIAMETER	INLET	JETS
BC-H9-C	40k psi	8 gpm	78 in.	1.8 in.	9/16 HP	4 x OS7
	2800 bar	30 lpm	200 mm	46 mm		
BC-H9LF-C	40k psi	4 gpm	78 in.	1.8 in.	9/16 HP	4 x OS7
	2800 bar	15 lpm	200 mm	46 mm		

Barracuda 40k psi - Jetting Chart

		OS7 NOZZLE ID in inches										
		.014	.015	.016	.017	.018	.019	.020	.021	.022	.023	.024
PRESSURE in K psi	32		3.1	3.5		3.9	4.4	4.8	5.4	5.9	6.5	
	36	2.9	3.3	3.6		4.1	4.6	5.1	5.6	6.2		
	40	3.0	3.5				4.3	4.8	5.4			
BC-H9LF-C Jetting Flow GPM								BC-H9-C Jetting Flow in GPM				



ADVANCED PRESSURE SYSTEMS

1-877-290-4277 ▲ FAX: 281-290-9952

www.advancedpressuresystems.com

E-mail orders: sales@advancedpressuresystems.com

