

Extension Nipples

Put Your Nozzle Tips Close to the Work

Precision-machined Stainless Nipples

Maximize your jet power and removal rates by placing your jets close to the target surface. Extension nipples also improve jet quality.

- Durable stainless steel construction
- Sizes in stock for all StoneAge® tools
- Makes smaller pumps capable of bigger jobs



BJV cleaning pipe with four extensions added.



SA 567-P4P2

Fits 1/4 npt ports
AP2 Attack Tips
15k psi

SA 356-P8P4

Fits 1/2 npt ports
AP4 Attack Tips
15k psi

SA 577-G12P4

Fits G12 ports
AP4 Attack Tips
20k psi

SA 569-G9S6

Fits G9 ports
OS6 Sapphire Tips
40k psi

Nipple Extension Specifications

TYPE	PART #	MAWP	THREADS	OD	ID
9/16 MP Tubing	SA 567-P4P2*	20k psi 1400 bar	1/4 nptm, 1/8 nptf	.563 in. 14.3 mm	.312 in. 7.9 mm
9/16 MP Tubing	SA 567-M9P2	20k psi 1400 bar	9/16 MP, 1/8 nptf	.563 in. 14.3 mm	.312 in. 7.9 mm
9/16 MP Tubing	SA 567-M9M9	20k psi 1400 bar	9/16 MP, 9/16 MP	.563 in. 14.3 mm	.312 in. 7.9 mm
1/2 Sched.160 Pipe	SA 356-P8P4**	15k psi 1000 bar	1/2m npt, 1/4 nptf	.840 in. 21.3 mm	.470 in. 11.9 mm
1/2 Sched.160 Pipe	SA 356-P8P8	15k psi 1000 bar	1/2m npt, 1/2 nptm	.840 in. 21.3 mm	.470 in. 11.9 mm
3/4 Sched.160 Pipe	SA 366-P12P12	15k psi 1000 bar	3/4m npt, 3/4m npt	1.05 in. 26.7 mm	.610 in. 15.5 mm
3/4 MP Tubing	SA 577-M12M12	20k psi 1400 bar	3/4 MP, 3/4 MP	.750 in. 19.1 mm	.438 in. 11.1 mm
3/4 MP Tubing	SA 577-M12P4	20k psi 1400 bar	3/4 MP, 1/4 nptf	.750 in. 19.1 mm	.438 in. 11.1 mm
3/4 MP Tubing	SA 577-G12P4**	20k psi 1400 bar	3/4 G12, 1/4 nptf	.750 in. 19.1 mm	.438 in. 11.1 mm
9/16 HP Tubing	SA 569-G9S6*	40k psi 2800 bar	9/16 G9, 3/8-24f	.563 in. 14.3 mm	.188 in. 4.8 mm

Notes: npt = National Pipe Thread MP = Cone & Thread Connection G12 tip for BJV 20k psi

* Standard Lengths - 2, 3, 4, 8 in. (51, 76, 101, 203 mm)

** Standard Lengths - 3, 4, 6, 8, 10, 12 in. (76, 101, 152, 203, 254, 305 mm)



www.advancedpressuresystems.com

Toll Free in North America:
1 (877) 290-4277 or (281) 290-9950



EXTENSION NIPPLES