


# 15k-20k psi Free Spinners

## SG-30™ Free Spinners

### SG-30™ Free Spinner



Radiused arms for powerful and effective jets.

### Jet-Powered Rotation

The **SG-30™ Free Spinner** tools provide a simple, self-rotating solution to surface cleaning and preparation. It uses 4 jet arms for excellent jet quality and a balanced, stable, self-rotating assembly. It is available in either 18" or 24" jet path diameters and features a universal mounting block and replaceable **AP4 Nozzle Tips**.



### Diverse Applications

**StoneAge®** has designed numerous systems for specialty cleaning operations. The image at left shows one such application for cleaning conveyor belts. Other applications include skids for boiler cleaning, airport runways, belts, screens and coatings, as well as degreasing and decontaminating concrete.

Below: An **SG-30™** cleaning a conveyor. Also see our **BLASTRACKS™** on page 11.



- **Self-rotating assembly**
- **18" or 24" jet path diameter**
- **Radiused arms enhance jets**
- **Replaceable nozzle tips**
- **Includes aluminum mounting block**
- **Balanced, stable rotation**

### SG-30™ Free Spinner Specifications

MODEL	MAX. PRES.	FLOW	JET PATH	ROTATION SPEED	WEIGHT	HEIGHT
<b>SG-30-P12™</b>	15k psi	50 gpm	18 or 24 in	300-1000 rpm	25 lbs	13 in.
	1000 bar	190 lpm	460 or 620 mm	300-1000 rpm	11.3 kg	330 mm
<b>SG-30-M12™</b>	20k psi	50 gpm	18 or 24 in	300-1000 rpm	26 lbs	13 in.
	1400 bar	190 lpm	460 or 620 mm	300-1000 rpm	11.3 kg	330 mm