







**13mm Type M Rubber Waterblast
APS #43-009-050**

Part Number	Min. I.D.	Max. O.D.	Working Pressure	Burst Pressure	Min. Bend Radius	Weight	
#							
	In. / mm	In. / mm	PSI / Bar	PSI / Bar	In. / mm	Lbs./Ft.	kg/m
	0.50" 12.7 mm	1.160" 29.5 mm	20,000 1379	50,000 3448	8.0" 203 mm	1.15	0.521


Temperature Range: -40° F and +200° F (-40° C and +90° C). Contact APS for temperatures outside this range.

Fittings: See below.

Construction: Synthetic oil-resistant rubber core reinforced with 4 layers of high tensile carbon steel wire with a synthetic oil-resistant outer cover.

Applications: Waterblasting.

**Example: 43-009-050 is a Rubber Waterblast hose
1" NPT (M) x 1" NPT (M) x 50 feet long**

End Fitting Code	Thread	Overall Length	Diam. R / Hex Size H	MAWP PSI/Bar	Illustration
13mm Type M	1"-12	A 4.25"/108 mm	H 1.25"/32 mm	20,000 1379	



PARKER POLYFLEX
Stocking Supplier

www.advancedpressuresystems.com
Toll Free in North America:
1 (877) 290-4277 or (281) 290-9950

