








**2025ST Flex Lances
APS #40-035 Parker Polyflex Hose - Black Jacket**

Part Number	Min. I.D.	Max. O.D.	MAWP with 2.5:1 Safety Factor	MAWP with 4:1 Safety Factor	Min. Burst Pressure	Min. Bend Radius	Weight	
#								
	In. / mm	In. / mm	PSI / Bar	PSI / Bar	PSI / Bar	In. / mm	Lbs./Ft.	kg/m
2245N-16V30	1.00" 25 mm	1.34" 34 mm	6,380 440	3,990 275	15,950 1100	11.02" 280	0.78	1.16




Construction: Polyamide core tube, high strength wire reinforced and a polyamide outer cover.

Applications: Lightweight, chemical resistant hose used to replace steel pipe and rubber hose for hydraulic test systems using synthetic and phosphate ester fluids, such as Skydrol® Fluids and gas transfer service.

Temperature Range: -40° F and +140° F (-40° C and +60° C). Contact Polyflex for temperatures outside this range.

Fittings: See below. Parker ProLance®.

Example: **40-035-1616-025 is a 2025ST 1" NPT (M) x 1" NPT (M) x 25 feet long**

End Fitting Code	Thread	Overall Length	Diam. R / Hex Size H	MAWP PSI/Bar	Illustration
NPT (M) 16	1" NPT	A 4.10"/104 mm	H 1.42"/36 mm	6,380 440	



PARKER POLYFLEX
Stocking Supplier

www.advancedpressuresystems.com

**Toll Free in North America:
1 (877) 290-4277 or (281) 290-9950**

