









2106ST Flex Lances
 APS #40-010 Parker Polyflex Hose - Black Jacket

Part Number	Min. I.D.	Max. O.D.	MAWP with 2.5:1 Safety Factor	MAWP with 4:1 Safety Factor	Min. Burst Pressure	Min. Bend Radius	Weight	
#								
	In. / mm	In. / mm	PSI / Bar	PSI / Bar	PSI / Bar	In. / mm	Lbs./Ft.	kg/m
2380N-04V00	0.25" 6 mm	0.53" 13 mm	16,240 1120	10,150 700	40,600 2800	2.76" 70	0.22	0.33




Construction: Polyamide core tube, high strength wire reinforced and a polyurethane outer cover.

Applications: Small diameter, low volumetric expansion hose. Ideal for pressure testing, portable hydraulic tools that require extreme kink resistance and maximum flexibility. Available in long single lengths and in Twin-Line construction.

Temperature Range: -40° F and +140° F (-40° C and +60° C). Contact Polyflex for temperatures outside this range.

Fittings: See below.

Example: **40-010-1010-025 is a 2106ST 3/8" NPT (M) x 3/8" NPT (M) x 25 feet long**

End Fitting Code	Thread	Overall Length	Diam. R / Hex Size H	MAWP PSI/Bar	Illustration
NPT (M)		A	H		
10	3/8" NPT	2.72"/69 mm	0.75"/19 mm	15K/1034	
09	1/4" NPT	2.62"/67 mm	0.63"/16 mm	15K/1034	



PARKER POLYFLEX
 Stocking Supplier

www.advancedpressuresystems.com
Toll Free in North America:
1 (877) 290-4277 or (281) 290-9950

