









**2108ST Flex Lances
APS #40-008 Parker Polyflex Hose - Black Jacket**

| Part Number | Min. I.D. | Max. O.D. | MAWP with 2.5:1 Safety Factor | MAWP with 4:1 Safety Factor | Min. Burst Pressure | Min. Bend Radius | Weight | |
|-------------|---|---|---|---|---|---|---|------|
| # |  |  |  |  |  |  |  | |
| | In. / mm | In. / mm | PSI / Bar | PSI / Bar | PSI / Bar | In. / mm | Lbs./Ft. | kg/m |
| 2380N-05V71 | 0.32" 8 mm | 0.62" 16 mm | 13,600 938 | 8,500 586 | 34,000 2345 | 3.50" 89 mm | 0.20 | 0.30 |

Construction: Polyamide core tube, high strength wire reinforced and a polyurethane outer cover.


Applications: Hydraulic tools, gas transfer, offshore chemical injection service and high pressure testing of equipment.

Fittings: See below.



Temperature Range: -40° F and +140° F (-40° C and +60° C). Contact Polyflex for temperatures outside this range.

Example: **40-008-1010-025 is a 2108ST 3/8" NPT (M) x 3/8" NPT (M) x 25 feet long**

| End Fitting Code | Thread | Overall Length | Diam. R / Hex Size H | MAWP PSI/Bar | Illustration |
|------------------|----------|----------------|----------------------|--------------|---|
| NPT (M) | | A | H | |  |
| 09 | 1/4" NPT | 2.78"/71 mm | 0.63"/16 mm | 13,600 | |
| 10 | 3/8" NPT | 2.96"/75 mm | 0.75"/19 mm | 938 | |