








2206ST Flex Lances
APS #40-036 Parker Polyflex Hose - Black Jacket


Part Number	Min. I.D.	Max. O.D.	MAWP with 2.5:1 Safety Factor	MAWP with 4:1 Safety Factor	Min. Burst Pressure	Min. Bend Radius	Weight
#							
	In. / mm	In. / mm	PSI / Bar	PSI / Bar	PSI / Bar	In. / mm	Lbs./Ft. kg/m
2390N-04V10	0.25" 6 mm	0.52"/13 mm	12,000 828	7,500 517	30,000 2069	3.00" 76	0.18 0.27

Construction: Polyamide core tube, high tensile strength wire reinforced and a polyurethane outer cover.


Applications: Small diameter, low volumetric expansion hose with sea-water resistant cover. Ideal for pressure testing, portable hydraulic tools and hydraulic controls.

Fittings: See below.

Example: **40-036-1010-025 is a 2206ST 3/8" NPT (M) x 3/8" NPT (M) x 25 feet long**



Temperature Range: -40° F and +140° F (-40° C and +60° C). Contact Polyflex for temperatures outside this range.

End Fitting Code	Thread	Overall Length	Diam. R / Hex Size H	MAWP PSI/Bar	Illustration
NPT (M)		A	H	12,000	
10	3/8" NPT	2.72"/69 mm	0.75"/19 mm	828	
09	1/4" NPT	2.38"/60 mm	0.63"/16 mm		