









2213ST Flex Lances
APS #40-011 Parker Polyflex Hose - Blue Jacket

Part Number	Min. I.D.	Max. O.D.	MAWP with 2.5:1 Safety Factor	MAWP with 4:1 Safety Factor	Min. Burst Pressure	Min. Bend Radius	Weight	
#								
	In. / mm	In. / mm	PSI / Bar	PSI / Bar	PSI / Bar	In. / mm	Lbs./Ft.	kg/m
2390N-08V12	0.50" 13 mm	0.81" 21 mm	10,400 717	6,500 448	26,000 1793	4.00" 102 mm	0.38	0.57

Construction: Polyamide core tube, high strength wire reinforced and a polyurethane outer cover.


Applications: Low volumetric expansion hose with sea-water resistant cover. Used in sub-sea hydraulic B.O.P. control systems, and in long lengths for pipe cleaning applications.

Fittings: See below.



Temperature Range: -40° F and +140° F (-40° C and +60° C). Contact Polyflex for temperatures outside this range.

Example: **40-011-1212-025 is a 2213ST 1/2" NPT (M) x 1/2" NPT (M) x 25 feet long**

End Fitting Code	Thread	Overall Length	Diam. R / Hex Size H	MAWP PSI/Bar	Illustration
NPT (M) 12	1/2" NPT	A 3.35"/85 mm	H 0.87"/22 mm	10,400 717	
Type M (F) Swivel 43	1"-12	A 3.20"/81 mm	H 1.25"/32 mm	10,400 717	