







4006ST Flex Lances
APS #40-016 Parker Polyflex Hose - Gray Jacket

Part Number	Min. I.D.	Max. O.D.	Max. Working Pressure	Min. Burst Pressure	Min. Bend Radius	Weight	
#							
	In. / mm	In. / mm	PSI / Bar	PSI / Bar	In. / mm	Lbs./Ft.	kg/m
2440N-04V37	0.25" 6 mm	0.50" 13 mm	23,780 1640	59,450 4100	6.10" 155	0.22	0.33






Construction: Polyamide core tube, high strength wire reinforced and a polyamide outer cover.

Applications: Small diameter, chemical resistant hose for hydraulic tools, pressure testing, offshore chemical injection and high pressure heat exchanger tube cleaning in petrochemical and power plants.

Temperature Range: -40° F and +140° F (-40° C and +60° C). Contact Polyflex for temperatures outside this range.

Fittings: See below.

Example: **40-016-2239-025 is a 4006ST 3/8"-24 LH Nozzle Nipple x 9/16"-18 Type M x 25 feet long**

End Fitting Code	Thread	Overall Length	Diam. R / Hex Size H	MAWP PSI/Bar	Illustration
NPT (M) 53 09	1/8" NPT 1/4" NPT	A 2.50"/64 mm 2.61"/66 mm	H 0.63"/16 mm 0.63"/16 mm	15,000 1034	
Type M (F) Swivel 39	9/16"-18	A 2.63"/67 mm	H 0.75"/19 mm	23,780 1640	
Male Water Jetting Nozzle Nipple ProLance* 22 24	3/8"-24 LH 3/8"-24 RH	A 2.60"/66 mm 2.60"/66 mm	R 0.590"/15 mm 0.590"/15 mm	20,000 1379	
Female Water Jetting ProLance* 59 23	3/8"-24 LH 3/8"-24 RH	A 1.83"/46 mm 1.83"/46 mm	R 0.590"/15 mm 0.590"/15 mm	20,000 1379	