








4008ST Flex Lances
APS #40-027 Parker Polyflex Hose - Gray Jacket

Part Number	Min. I.D.	Max. O.D.	Max. Working Pressure	Min. Burst Pressure	Min. Bend Radius	Weight	
#							
	In. / mm	In. / mm	PSI / Bar	PSI / Bar	In. / mm	Lbs./Ft.	kg/m
2440D-05V37	0.32" 8 mm	0.61" 15 mm	21,750 1500	54,500 3759	6.88" 175 mm	0.30	0.45

Construction: Polyoxymethylene core tube, high strength wire reinforced and a polyamide outer cover.






Applications: Chemical resistant hose for hydraulic tools, pressure testing of offshore equipment and high pressure heat exchanger tube cleaning in petrochemical and power plants.

Fittings: See below.



Temperature Range: -40° F and +140° F (-40° C and +60° C). Contact Polyflex for temperatures outside this range.

Example: **40-027-4141-025 is a 4008ST 3/4"-16 Type M x 3/4"-16 Type M x 25 feet long**

End Fitting Code	Thread	Overall Length	Diam. R / Hex Size H	MAWP PSI/Bar	Illustration
NPT (M) 09 10	1/4" NPT 3/8" NPT	A 2.78"/71 mm 2.96"/75 mm	H 0.63"/16 mm 0.75"/19 mm	15,000 1034	
Type M (F) Swivel 41	3/4"-16	A 2.95"/75 mm	H 1.00"/25 mm	21,750 1500	
MP (M) Tube Nipple 27 29	9/16"-18 LH 3/4"-16 LH	A 3.83"/97 mm 3.74"/95 mm	R 0.95"/24 mm 0.95"/24 mm	20,000 1379	
Male Water Jetting Nozzle Nipple ProLance* 57 63	9/16"-18 LH 9/16"-18 RH	A 2.71"/69 mm 2.71"/68 mm	R 0.687"/17 mm 0.687"/17 mm	26,100 1800	
Female Water Jetting ProLance* 67 66	9/16" - 18 LH 9/16" - 18 RH	2.60"/66 mm 2.60"/66 mm	R 0.687"/17 mm 0.687"/17 mm	20,000 137.9	
BSP Female Swivel Nozzle 92	3/8" BSPP	2.90"/74 mm	H 1.06"/27 mm	21,750 150.0	