








4010ST Flex Lances
APS #40-029 Parker Polyflex Hose - Black Jacket

Part Number	Min. I.D.	Max. O.D.	Max. Working Pressure	Min. Burst Pressure	Min. Bend Radius	Weight
#						
	In. / mm	In. / mm	PSI / Bar	PSI / Bar	In. / mm	Lbs./Ft. kg/m
2440N-06V91	0.40" 10 mm	0.77" 20 mm	20,300 1400	50,750 3500	7.50" 191 mm	0.47 0.70




Construction: Polyoxymethylene core tube, high strength wire reinforced and a polyamide outer cover.

Applications: Chemical resistant hose for hydraulic tools, pressure testing of offshore equipment and high pressure heat exchanger tube cleaning in petro chemical and power plants.

Fittings: See below.

Temperature Range: -40° F and +140° F (-40° C and +60° C). Contact Polyflex for temperatures outside this range.

Example: **40-029-4141-025 is a 4010ST 3/4"-16 Type M x 3/4"-16 Type M x 25 feet long**

End Fitting Code	Thread	Overall Length	Diam. R / Hex Size H	MAWP PSI/Bar	Illustration
Type M (F) Swivel 41	3/4"-16	A 2.95"/75 mm	H 1.00"/25 mm	21,750 1500	
MP (M) Tube Nipples 27	9/16"-18 LH	A 3.80"/97 mm	H 1.22"/31 mm	20,000 1379	