







4020ST Flex Lances
APS #40-039 Parker Polyflex Hose - Gray Jacket

Part Number	Min. I.D.	Max. O.D.	Max. Working Pressure	Min. Burst Pressure	Min. Bend Radius	Weight	
#							
	In. / mm	In. / mm	PSI / Bar	PSI / Bar	In. / mm	Lbs./Ft.	kg/m
2440N-12V37	0.81" 21 mm	1.19" 30 mm	14,500 1000	37,500 2586	10.00" 254 mm	0.93	1.39





Construction: Polyamide core tube, high strength wire reinforced and a polyamide outer cover.

Applications: Flexible, chemical resistant alternative to steel pipe for applications such as waterblasting, hydrodemolition, gas transfer, hydraulic workover and chemical injection.

Fittings: See below.

Temperature Range: -40° F and +140° F (-40° C and +60° C). Contact Polyflex for temperatures outside this range.

Example: **40-039-1616-025 is a 4020ST 1" NPT (M) x 1" NPT (M) x 25 feet long**

End Fitting Code	Thread	Overall Length	Diam. R / Hex Size H	MAWP PSI/Bar	Illustration
NPT (M) 14 16	3/4" NPT 1" NPT	A 4.75"/121 mm 4.90"/124 mm	H 1.38"/35 mm 1.38"/35 mm	10,000 690	
Type M (F) Swivel 45	1-5/16"-12	A 4.15"/105 mm	H 1.50"/38 mm	15,000 1034	
MP (M) Tube Nipple 30	1"-14 LH	A 5.39"/137 mm	R 1.56"/40 mm	15,000 1034	