








**6004ST Flex Lances**  
**APS #40-025 Parker Polyflex Hose - Blue Jacket**

Part Number	Min. I.D.	Max. O.D.	Max. Working Pressure	Min. Burst Pressure	Min. Bend Radius	Weight	
#							
	In. / mm	In. / mm	PSI / Bar	PSI / Bar	In. / mm	Lbs./Ft.	kg/m
<b>2640D-025V32</b>	0.16" 4 mm	0.48" 12 mm	40,600 2800	101,500 7000	5.50" 140 mm	0.20	0.30





**Construction:** Polyoxymethylene core tube, high strength wire reinforced and a polyamide outer cover.

**Applications:** Small diameter flexible hose, ideal for tight routing applications such as hydraulic tools, and high pressure heat exchanger tube cleaning in petrochemical and power plants. Especially suitable for hydraulic pre-tensioning equipment, specialized pressure fitted sleeve and coupling removal equipment. Pressure testing, operations of portable jacks and remote pressure sensing devices.

**Temperature Range:** -40° F and +140° F (-40° C and +60° C). Contact Polyflex for temperatures outside this range.

**Fittings:** See below.

**Example:** **40-025-2539-025 is a 6004ST 3/8"-24 LH Nipple x 9/16"-18 Type M x 25 feet long**

End Fitting Code	Thread	Overall Length	Diam. R / Hex Size H	MAWP PSI/Bar	Illustration
Type M (F) Swivel 39	9/16"-18	<b>A</b> 3.13"/79 mm	<b>H</b> 0.69"/18 mm	40,600 2800	
HP (M) Tube Nipple 21 25	1/4"-28 LH 3/8"-24 LH	<b>A</b> 3.50"/89 mm 3.95"/100 mm	<b>R</b> 0.68"/17 mm 0.68"/17 mm	40,600 2800	
HP (F) Swivel Fitting 46	9/16"-18	<b>A</b> 3.13"/79 mm	<b>H</b> 0.69"/18 mm	40,600 2800	