







6104ST Flex Lances
APS #40-043 Parker Polyflex Hose - Black Jacket

| Part Number | Min. I.D. | Max. O.D. | Max. Working Pressure | Min. Burst Pressure | Min. Bend Radius | Weight |
|--------------|---|---|---|--|---|---|
| # |  |  |  |  |  |  |
| | In. / mm | In. / mm | PSI / Bar | PSI / Bar | In. / mm | Lbs./Ft. kg/m |
| 2740D-025V30 | 0.16" 4 mm | 0.48" 12 mm | 45,000 3103 | 112,500 7759 | 4.75" 121 mm | 0.21 0.31 |






Temperature Range: -40° F and +140° F (-40° C and +60° C). Contact Polyflex for temperatures outside this range.

Fittings: See below.

Construction: Polyoxymethylene core tube, high strength wire reinforced and a polyamide outer cover.

Applications: Small Diameter flexible hose, ideal for tight routing applications such as hydraulic tools, and high pressure heat exchanger tube cleaning in petrochemical and power plants. Especially suitable for hydraulic pre-tensioning equipment, specialized pressure fitted sleeve and coupling removal equipment. Pressure testing operations of portable jacks and remote pressure sensing devices.

Example: **40-043-3939-025 is a 6104ST 9/16"-18 Type M x 9/16"-18 Type M x 25 feet long**

| End Fitting Code | Thread | Overall Length | Diam. R / Hex Size H | MAWP PSI/Bar | Illustration |
|--------------------------|--------------------------|---|----------------------------|----------------|---|
| Type M (F) Swivel 39 | 9/16"-18 | A 3.13"/79 mm | H 0.69"/18 mm | 45,000 3103 |  |
| HP (M) Tube Nipple 21 25 | 1/4"-28 LH 3/8"-24 LH | A 3.50"/89 mm 3.95"/100 mm | R 0.68" 0.68" | 45,000 3103 |  |
| HP (F) Swivel Fitting 46 | 9/16"-18 | A 3.13"/79 mm | H 0.69"/18 mm | 45,000 3103 |  |