







6104ST Flex Lances
APS #40-043 Parker Polyflex Hose - Black Jacket

Part Number	Min. I.D.	Max. O.D.	Max. Working Pressure	Min. Burst Pressure	Min. Bend Radius	Weight
#						
	In. / mm	In. / mm	PSI / Bar	PSI / Bar	In. / mm	Lbs./Ft. kg/m
2740D-025V30	0.16" 4 mm	0.48" 12 mm	45,000 3103	112,500 7759	4.75" 121 mm	0.21 0.31





Temperature Range: -40° F and +140° F (-40° C and +60° C). Contact Polyflex for temperatures outside this range.

Fittings: See below.

Construction: Polyoxymethylene core tube, high strength wire reinforced and a polyamide outer cover.

Applications: Small Diameter flexible hose, ideal for tight routing applications such as hydraulic tools, and high pressure heat exchanger tube cleaning in petrochemical and power plants. Especially suitable for hydraulic pre-tensioning equipment, specialized pressure fitted sleeve and coupling removal equipment. Pressure testing operations of portable jacks and remote pressure sensing devices.

Example: **40-043-3939-025 is a 6104ST 9/16"-18 Type M x 9/16"-18 Type M x 25 feet long**

End Fitting Code	Thread	Overall Length	Diam. R / Hex Size H	MAWP PSI/Bar	Illustration
Type M (F) Swivel 39	9/16"-18	A 3.13"/79 mm	H 0.69"/18 mm	45,000 3103	
HP (M) Tube Nipple 21 25	1/4"-28 LH 3/8"-24 LH	A 3.50"/89 mm 3.95"/100 mm	R 0.68" 0.68"	45,000 3103	
HP (F) Swivel Fitting 46	9/16"-18	A 3.13"/79 mm	H 0.69"/18 mm	45,000 3103	