








6105ST Flex Lances
APS #40-023 Parker Polyflex Hose - Black Jacket

Part Number	Min. I.D.	Max. O.D.	Max. Working Pressure	Min. Burst Pressure	Min. Bend Radius	Weight
#						
	In. / mm	In. / mm	PSI / Bar	PSI / Bar	In. / mm	Lbs./Ft. kg/m
2740D-03V30	0.20" 5 mm	0.52" 13 mm	40,600 2800	101,500 7000	6.00" 152 mm	0.32 0.48

Construction: Polyamide core tube, high strength wire reinforced and a polyamide outer cover.



Applications: Flexible, chemical resistant alternative to steel pipe delivery hose in waterblasting, hydrodemolition systems, chemical injection and gas transfer, oil field wireline logging services, and pressure testing.



Temperature Range: -40° F and +140° F (-40° C and +60° C). Contact Polyflex for temperatures outside this range.

Fittings: See below.

Example: 40-023-3939-025 is a 6105ST 9/16"-18 Type M x 9/16"-18 Type M x 25 feet long

End Fitting Code	Thread	Overall Length	Diam. R / Hex Size H	MAWP PSI/Bar	Illustration
Type M (F) Swivel 39	9/16"-18	A 3.20"/81 mm	H 0.68"/17 mm	40,600 2800	
HP (M) Tube Nipple 25 28	3/8"-24 LH 9/16"-18 LH	A 4.05"/103 mm 4.42"/112 mm	R 0.82"/21 mm 0.82"/21 mm	40,600 2800	
HP (F) Swivel Fitting 46	9/16"-18	A 3.20"/81 mm	H 0.68"/17 mm	40,600 2800	